I claim:

1. An apparatus for the transportation of a large, heavy or unwieldy article by two users comprising:

a support strap of longer extent than said article for running end-to-end underneath and thereby cradling said article, said support strap having distal handles at each end for gripping by the respective users; and

a plurality of rigid cradle assemblies adjustably attached along said support strap, each cradle assembly comprising a flat support member having upwardly angled edges for cradling said article and providing lateral support therefor, and a plurality of strap retaining slots formed centrally along said flat support member transverse to said edges for threading said support strap there through.

2. The apparatus for the transportation of a large, heavy or unwieldy article by two users according to claim 1 wherein said support strap is fabricated of nylon.

3. The apparatus for the transportation of a large, heavy or unwieldy article by two users according to claim 1, wherein said plurality of cradle assemblies are each integrally-molded of plastic.

4. The apparatus for the transportation of a large, heavy or unwieldy article by two users according to claim 1, wherein the distal handles of said support strap are formed by sewing said strap onto itself at both ends.

5. The apparatus for the transportation of a large, heavy or unwieldy article by two users according to claim 4, wherein said support strap is sewn onto itself at both ends in a cris-cross pattern

6. A method for the transportation of a large, heavy or unwieldy article by two users comprising the steps of:

providing an apparatus including a support strap of longer extent than said article for running end-to-end underneath and thereby cradling said article, said support strap having distal handles at each end for gripping by the respective users, and a plurality of cradle assemblies adjustably attached along said support strap, each cradle assembly comprising a flat support member with upwardly angled edges for cradling said article and providing lateral support therefor, and a plurality of strap retaining slots formed centrally along said flat support member transverse to said edges for threading said support strap there through;

cradling said article in said plurality of cradle assemblies; and

lifting and transporting said article cradled in said plurality of cradle assemblies via use of said support strap.